FREE SAMPLE

The opening pages of

1963 Harley-Davidson Panhead Buyer's Guide

Read these pages exactly as they appear in the full guide.
Nothing here is rewritten or summarised — it is the product itself,
so you can judge the depth before you spend a dollar.

The full guide: https://ironheadguides.com/product/IH-HARLEY-PANHEAD-1963

IronHead — instant PDF download after checkout.

IRONHEAD

1963 Harley-Davidson Panhead — Factory-Correct Restoration Guide

IronHead single-year guide · Model year 1963 only · Covers all 1963 Panhead Big Twins — the Duo-Glide: FL, FLF, FLH, FLHF · The 1962 Panhead and all later years are out of scope except where differences are noted

Factory-correct restoration guides for classic motorcycles

KEY FACTS AT A GLANCE

- **Model year covered:** 1963 only — the Duo-Glide: FL, FLF (foot shift), FLH, FLHF Super Sport.
- **Engine:** 74ci (73.66 cu in) 45-degree air-cooled OHV V-twin; 3-7/16 x 3-31/32 in bore x stroke; 7.25:1 compression (FL), 8.0:1 (FLH). Aluminum heads, hydraulic lifters — with NEW external oil lines to the heads.
- **New for 1963:** external oil lines to the cylinder heads (revised cylinders and right crankcase to feed them) — the fix for top-end oiling; wider rear brake hub and wider brake shoes; round turn-signal housings; fiberglass saddlebags; new bar-and-shield tank emblem; revised taillight.
- **Ignition:** 6-volt battery; dual-point, single-fire timer with individual condensers; manual advance; kick start only.
- **Transmission:** 4-speed constant-mesh; hand shift/foot clutch standard, foot shift/hand clutch optional.
- **Chassis:** Duo-Glide swingarm frame; Hydra-Glide telescopic fork; 8-inch front drum (mechanically operated); wider hydraulically actuated rear drum.
- **Wheels/tires:** Wire-spoked wheels; 5.00 x 16 fitment (standard Big Twin fitment; confirm against the factory service manual for the exact year).
- **Dimensions:** 61-inch wheelbase.
- **1963 colors:** Black, Tango Red, Horizon Metallic Blue, Police Silver, Police Birch White (the stated colors shown with Birch White tank panels); extra-cost Hi-Fi Red, Hi-Fi Purple, Hi-Fi Turquoise.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

- **Identification:** No frame VIN — the engine serial (left case, between the cylinders, e.g. 63FL1234) is the ownership number. Belly numbers on both crankcase halves must match each other.
- **Production:** FL 1,096; FLF 950; FLH 100; FLHF 2,100 — 4,246 across the listed models (compiled figures; Harley-Davidson published no official year totals).
- **1963 price new:** $1,360 (FL); $1,425 (FLH).
- **Key 1963-only details:** the external head-oil lines are the year's mechanical signature — revised cylinders and right case to feed them; the wider rear brake; the fiberglass bags; the new bar-and-shield emblem.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

1. Manufacturer history: Harley-Davidson

Harley-Davidson was founded in Milwaukee, Wisconsin, in 1903 by William S. Harley and Arthur Davidson, with Walter and William A. Davidson joining the effort. The first factory went up in 1906; the first V-twin appeared in 1909. Through the 1910s and 1920s Harley built its name on V-twins and racing success; the 45-cubic-inch flathead models of the 1930s kept the company alive through the Depression, and the 1936 EL Knucklehead brought overhead valves to the Big Twin line.

By 1963 the Panhead was fifteen years old and Milwaukee was still improving it: the external oil lines to the heads finally gave the top end the lubrication the internal passages had never quite delivered, and the wider rear brake gave the Duo-Glide the stopping power its weight demanded. The engine that had debuted in 1948 was being perfected in its final years.

The Panhead era that followed is the backbone of this brand: the 1965 Electra Glide added electric start and 12-volt electrics. The Panhead ran from 1948 through the 1965 model year, when the Shovelhead took over for 1966.

For the restorer, the authority is the factory literature: the Harley-Davidson Panhead service manuals and the year parts catalogs, backed by Bruce Palmer's *How to Restore Your Harley-Davidson*, Greg Field's *Original Harley-Davidson Panhead*, and the production research compiled by the Panhead & Flathead Site. This guide cites those sources throughout.

2. Model history: the Panhead Big Twin, 1948–1965

The 1948 Panhead kept the Knucklehead's proven crankcases, flywheels, and gear train and changed everything above the cylinders: finned aluminum heads with bronze valve seats and steel inserts, pushrod-operated hydraulic lifters, and redesigned rocker arms under pan-shaped covers. 1949 brought the Hydra-Glide telescopic fork, the 8-inch front drum, and the Brooks Stevens restyle; 1950 brought redesigned heads with enlarged ports; 1951 brought the two-piece cam, machined rocker sockets, and the Linkert M-74B; 1952 brought the foot-shift option, an all-high-compression lineup, and the end of the 61ci EL; 1953 relocated the hydraulic lifters below the pushrods and introduced the FLE Traffic Combination; 1954 was the Golden Anniversary year; 1955 introduced the FLH Super Sport; 1956 gave the FLH its "Victory" high-lift cam; 1957 was the last rigid year; 1958 introduced the Duo-Glide; 1959 refined it; 1960 brought the aluminum nacelle and the durability upgrades; 1961 brought the dual-point, single-fire ignition; 1962 brought the tombstone speedometer and the new dashboard.

1963 was the oiling year, part two: external oil lines to the cylinder heads, fed by revised cylinders and a revised right crankcase — the most effective top-end lubrication the Panhead ever had — plus the wider rear brake hub and shoes, round turn-signal housings, fiberglass saddlebags, and the new bar-and-shield tank emblem.

The model letters work like this. **FL** = 74ci high-compression (7.25:1). **FLH** = Super Sport — 8.0:1 compression, strengthened bottom end, the performance model. **S** = sidecar gearing. **F** (not first letter) = foot shift. **B** (1965) = electric start.

Year	What changed
1948	First Panhead: aluminum heads, hydraulic lifters, internal oiling; wishbone frame; springer fork (one year only); chromed pan covers (one year only); E/EL and F/FL.
1949	Hydra-Glide telescopic fork replaces the springer; Brooks Stevens restyle; front brake grows 7.25 to 8 inches; Harley-Davidson makes its own breaker points.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Year	What changed
1950	Redesigned heads with enlarged ports (about 10 percent more power); fixed-jet carburetor with revised jetting; remote oil filter; primary screws to 6/12 o'clock; die-cast fork sliders.
1951	Two-piece cam with ramps both sides; rocker arms machined with pushrod sockets; mid-year Linkert M-74B carburetor (stays through 1965); larger pinion shaft; script tank emblem.
1952	Foot-shift option (ELF/FLF); all Panheads high-compression; last year for the 61ci EL; rotating exhaust valves late-year; generator model 52.
1953	Lifters relocated below pushrods; FLE Traffic Combination introduced; 4-rib gearcase cover; 24-roller pinion shaft; revised generator; new muffler; 74-only lineup.
1954	Golden Anniversary brass medallion; tapered pinion shaft; Jubilee trumpet horn; first optional dual exhaust; winged fireball emblems; transitional frames.
1955	First FLH Super Sport — 8:1 compression, 60 hp @ 5,500 rpm, strengthened bottom end with Timken mains, larger oil pump, polished rocker covers; oval taillight; "V" emblem.
1956	FLH "Victory" high-lift cam and flow-through air cleaner (about 12 percent more power); redesigned right crankcase with new check-valve oiling path; new speedometer.
1957	Last rigid year: round Lucite tank emblem (first plastic emblem); plastic fender tip; polished aluminum rocker covers; steel-alloy valve guides from February 1; stronger springs from 57FLH4444.
1958	First Duo-Glide: swingarm rear suspension; step-down straight-leg frame; horseshoe oil tank; hydraulically actuated rear drum; thicker head fins; brush generator; O-ring intake seals.
1959	Arrow-Flite tank emblem; green neutral indicator on foot-shift dash; chrome front fender tip; black footboards; optional center stand; revised taillight lens.
1960	Two-piece aluminum headlight nacelle; Stellite-faced exhaust valves; rail-type oil-control rings; extra-heavy valve springs; revised clutch; new taillight.
1961	Dual-point, single-fire ignition with individual condensers; rear-cylinder timing mark added mid-year; revised pushrods; four-point-star tank badge; revised taillight.
1962	"Tombstone" speedometer; three round indicator lights on the dashboard; brushed-aluminum trim pieces; revised taillight.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Year	What changed
1963	**External oil lines to the cylinder heads (revised cylinders and right crankcase); wider rear brake hub and shoes; round turn-signal housings; fiberglass saddlebags; new bar-and-shield tank emblem; revised taillight.**
1964	Breather hole in the primary housing; oil-pressure switch; hollow hex timer adjuster; last year of the Duo-Glide.
1965	Electra Glide: electric start, 12-volt electrics, new frame, aluminum primary cover, automatic spark advance; last year of the Panhead.

The company context matters when judging a bike. The postwar boom made the late 1940s Harley's biggest years yet; by the mid-1950s British imports were pressuring the sporting end of the market (answered by the 1952 K-model and the 1957 Sportster), while the Big Twin settled into its long career as America's touring motorcycle. The 1969 AMF takeover came after the Panhead era; no Panhead left Milwaukee under AMF ownership.

3. What is unique about the 1963 Panhead

The 1963 is the external-oiling year — the only early-60s Panhead with the factory external oil lines to the heads, and the revised cylinders and right crankcase that feed them. The lines are visible, the cases are different, and the combination is the year's mechanical signature. A correct 1963 has the lines, the right cases, and the right cylinders — all three.

1963 details to get right:

- **External oil lines to the cylinder heads** — new for the year; the

single most visible 1963 engine detail.

- **Revised cylinders and revised right crankcase** to feed the lines — a

1963 with the lines but pre-1963 cases/cylinders is a retrofit, not a factory bike.

- **Wider rear brake hub and wider brake shoes** — the stopping-power

upgrade; check the hub width, not just the shoes.

- **Round turn-signal housings** — new shape for the year.
- **Fiberglass saddlebags** — new for 1963.
- **New bar-and-shield tank emblem; revised taillight.**

What did NOT exist in 1963 (common mix-ups):

- No oil-pressure switch or primary breather hole (1964), no 12-volt system

or electric start (1965).

1963 buyer cautions:

- **Retrofit versus factory.** The external lines were a known retrofit for

earlier bikes — a 1963's originality is in the cases and cylinders, not just the lines. Verify all three together.

- **Brake originality.** The wider hub is the 1963 tell — a narrow-hub

wheel on a 1963 is a swapped part.

- **Fiberglass bags.** Original 1963 fiberglass bags are fragile and often

replaced with later leather or reproduction — check the material and the mounting.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

4. Technical restoration data — 1963 Harley-Davidson Panhead

4.1 Frame and engine numbers (1963)

Pre-1970 Harleys carry no frame VIN — the engine number is the ownership number. It is stamped on the left crankcase between the cylinders, in the form year-digits + model letters + sequential number, for example:

```
63FLH1234
63 = model year | FLH = model | 1234 = sequential number
```

Foot-shift (F) and sidecar (S) suffixes may not appear in the stamped ownership serial even when the bike is a factory foot-shift or sidecar model. The frame carries only manufacturing stampings and casting numbers.

Belly numbers are stamped on the bottom of each crankcase half. They were stamped by the machinist to identify a matched pair of cases through line boring and final machining — the two halves must carry the SAME belly number, and the belly number has no direct relationship to the engine serial.

4.2 Engine specifications (1963)

Item	FL	FLH (Super Sport)
Configuration	45° air-cooled OHV V-twin; hydraulic lifters; aluminum heads; external head-oil lines	Same, strengthened bottom end
Displacement	73.66 cu in	73.66 cu in
Bore x stroke	3-7/16 x 3-31/32 in (87.3 x 100.8 mm)	Same
Compression ratio	7.25:1	8.0:1
Carburetor	Linkert M-74B	Linkert M-74B
Ignition	6-volt battery; dual-point, single-fire timer with individual condensers; manual advance	Same
Starting	Kick starter only	Same
Clutch	Dry multi-plate	Same
Lubrication	Dry sump; external oil lines to heads; revised cylinders and right case; gear-driven pump	Same; larger pump; Timken mains

Note: no factory output figure is documented for 1963 in the surviving factory literature consulted — the 1955–1958 figures are not carried forward here, and period advertising claims vary. Do not quote an output number for a 1963.

4.3 Carburetion and electrical

- Linkert M-74B with O-ring intake seals — rebuild with correct settings,

not a generic kit

- 6-volt battery ignition with the dual-point, single-fire timer and

individual condensers; verify charging under load

- Kick starter only; manual advance

SAMPLE EXCERPT — full guide available at the link on the cover sheet