FREE SAMPLE

The opening pages of

1976 Yamaha RD400 Restoration Guide

Read these pages exactly as they appear in the full guide.
Nothing here is rewritten or summarised — it is the product itself,
so you can judge the depth before you spend a dollar.

The full guide: https://ironheadguides.com/product/IH-YAMAHA-RD400-1976

IronHead — instant PDF download after checkout.

IRONHEAD

Factory-Correct Restoration Guides

Yamaha

RD400

Restoration Guide — Model Year 1976

Engine *399 cc air-cooled two-stroke reed-valve twin*	***Output*** *44 bhp @ 7,000 rpm*
Brakes *Front disc; rear disc or drum by wheel option (1976)*	***Weight / Tank*** *165 kg wet / 16.5 L tank (see notes)*

*Single-year edition — covers the **1976** model year only (RD400C). A companion to the Yamaha factory service manual, not a replacement: correct sequence, year-change points, measure-first checkpoints, finishes, fasteners and markings, parts interchange, and honest value guidance.*

US $29.95 • ironhead.polsia.app

SAMPLE EXCERPT — full guide available at the link on the cover sheet

About this guide

This is a **restoration companion to the Yamaha factory service manual, not a replacement** for it. You need both: the manual gives the full teardown procedures, torque tables and the wiring diagram; this guide gives you the correct **sequence**, the **model-year change points**, what to **measure before you clean anything**, what **not to do**, the **finishes, fasteners and markings** that make a restoration factory-correct, parts interchange, and honest value guidance.

Every numeric value in this guide is cited to a source in the spec tables. Anything the cited literature does not give a number for is omitted or flagged **[UNVERIFIED — not in factory literature]**. We never invent specifications.

This is a **single-year edition**: it covers the **1976 RD400** only. Do not apply its year-specific details to other years.

Scope: RD400 — model year 1976 (RD400C)

Yamaha Motor Co. — the context that matters

Yamaha Motor Co. built its reputation on two-strokes: from the 1955 YA-1 the company made light, rev-happy twins its signature, and the RD line carried the TZ racer formula (reed valves, seven ports, Autolube) onto the street (Hagerty Media; Rider Magazine).

For restoration purposes the RD naming matters: the letter after the model (RD350A, RD400C and so on) is the model-year revision, and US designations do not always match rest-of-world ones — the 1979 US Daytona 'F' is the standing warning (Wikipedia, Yamaha RD400).

Yamaha's parts system keys everything to the model-code prefix in the frame number (351-, 1A1-, 2V0- on these bikes). Order by prefix and year, never by model name alone.

Model history — RD400

The RD400 (US model years 1976-1979) grew the RD350 by stroke: a new crankshaft took stroke from 54 mm to 62 mm for 399 cc, with torque the real gain — about 30 lb-ft against the 350's 24 lb-ft (Visordown, Yamaha RD history / RD400 Bike Icon; autoevolution, Yamaha RD model pages).

Styling changed with it: a squared-off 'coffin' tank replaced the RD350's rounded tank (Visordown, Yamaha RD history / RD400 Bike Icon). US models had a smaller, slightly different-shaped tank than other markets (Wikipedia, Yamaha RD400).

The RD400C was the first motorcycle from a major manufacturer offered with cast wheels — as an option in 1976 alongside standard spoked wheels; the choice also decided the rear brake (Wikipedia, Yamaha RD400).

US ignition stayed with points until the Daytona Special; rest-of-world E models are credited with CDI from 1978 — the two statements sit in the same marque record and this guide flags the US position year by year rather than blending them (Wikipedia, Yamaha RD400).

The 1979 Daytona Special closed the US air-cooled RD line; emissions rules ended US sales and the liquid-cooled RD350LC line followed elsewhere (Wikipedia, Yamaha RD400; Mecum Auctions, 1979 RD400 Daytona Special lot record).

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Model identification — confirm what you have

Model-code prefixes settle the year: US RD400C/D bikes record 1A1- VINs (Hagerty records: 1976 1A1009049; 1977 1A1314106), and the 1979 US Daytona Special records 2V0- VINs (Hagerty records: 2V0001744 and others; Mecum lot engine no. 2V0001620). The US Daytona is designated 'F' in the USA only — it is not the rest-of-world RD400F (Wikipedia, Yamaha RD400). Read the prefix before anything else: ignition type, wheels and rear brake all follow from it.

This 1976: RD400C. Frame serial reference: 1A1- prefix (Hagerty record VIN 1A1009049)

Year-correct equipment: Documented 1976 sale example: Red exterior (Hagerty record, VIN 1A1009049); contemporary comment also notes blue and green bikes in 1976-77 (ADVrider owner discussion — treat as indicative, parts book governs). Chappy Red is the commonly documented C colour name in marque discussion.

Confirm the serial block **before ordering parts** — especially brakes, wheels, carburettors and electrics, which are year-specific on this model. A bike titled as one year but carrying another year's major parts is common after 40–60 years; trust the stampings, not the title.

> ***1976 at a glance:*** *Front disc; rear drum (spoked) or disc (cast-wheel option)*

Year-change register — what changed for 1976

Running changes across the model run, with why each matters to a restorer. Rows marked for this year are the ones that affect **your** parts ordering.

- Launch year (C). Longer-stroke 399 cc engine (62 mm stroke, new crankshaft) replaces the RD350 (Visordown, Yamaha RD history / RD400 Bike Icon).
- Squared-off 'coffin' tank replaces the rounded RD350 tank (Visordown, Yamaha RD history / RD400 Bike Icon).
- Wheels/brakes are an ordered pair on a C: standard spoked wheels come with a rear DRUM; the optional cast wheels — a production-bike first from a major maker — come with a rear DISC (Wikipedia, Yamaha RD400). Identify which your bike was built with before ordering either end.
- Points ignition on US bikes (Wikipedia, Yamaha RD400). Self-cancelling indicators fitted (speedo-pulse system).

Verified spec tables — 1976 RD400

Every row cites its source. Rows flagged [UNVERIFIED] are printed as found, not as factory-verified. Year band: RD400C.

ENGINE

Spec	Value	Unit	Source / notes
Engine type	Air-cooled two-stroke parallel twin, reed-valve (Torque Induction)		Wikipedia, Yamaha RD400 (spec infobox and model history)

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Spec	Value	Unit	Source / notes
Displacement	399	cc	Wikipedia, Yamaha RD400 (spec infobox and model history) (autoevolution lists 398 cc — same engine, rounding)
Bore x stroke	64 x 62	mm	Wikipedia, Yamaha RD400 (spec infobox and model history)
Compression ratio	6.2:1		Wikipedia, Yamaha RD400 (spec infobox and model history)
Max power (claimed)	44 @ 7,000	bhp @ rpm	Wikipedia, Yamaha RD400 (spec infobox and model history) (Bike magazine, May 1979, as cited; autoevolution quotes 44 @ 7,500 — conflict flagged)
Max torque (claimed)	41.1 (30.3 lb-ft) @ 6,500	N·m @ rpm	Wikipedia, Yamaha RD400 (spec infobox and model history)
Carburettors	2 x Mikuni 28 mm		autoevolution, Yamaha RD model pages (RD400C) / motorbike-search-engine.co.uk, Yamaha RD400 data (1978)
Lubrication	Autolube oil injection, separate tank and pump		Wikipedia, Yamaha RD400 (spec infobox and model history)
Transmission	6-speed, chain drive, kick start		Wikipedia, Yamaha RD400 (spec infobox and model history)

ELECTRICAL

Spec	Value	Unit	Source / notes
Ignition	Points (US, 1976-78); CDI — see year register (1978 E conflict; US Daytona 1979)		Wikipedia, Yamaha RD400 (spec infobox and model history)

CHASSIS

Spec	Value	Unit	Source / notes
Frame	Tubular twin-cradle steel		Wikipedia, Yamaha RD400 (spec infobox and model history)
Front brake	Single disc, 267 mm	mm	autoevolution, Yamaha RD model pages / motorbike-search-engine.co.uk, Yamaha RD400 data
Rear brake	1976: drum with spoked wheels, 267 mm disc with cast-wheel option; disc thereafter — see year register		Wikipedia, Yamaha RD400 (spec infobox and model history) / autoevolution, Yamaha RD model pages
Tyres	3.00 x 18 front / 3.50 x 18 rear (infobox); 1978 listing: 3.60 x 18 / 4.10 x 18 — conflict flagged		Wikipedia, Yamaha RD400 (spec infobox and model history) / motorbike-search-engine.co.uk, Yamaha RD400 data
Wheelbase	1,330	mm	Wikipedia, Yamaha RD400 (spec infobox and model history)
Wet weight	165 (364 lb, part-fuelled figure as cited)	kg	Wikipedia, Yamaha RD400 (spec infobox and model history)
Fuel capacity	16.5 (US tank smaller/different shape — exact US figure [UNVERIFIED])	L	Wikipedia, Yamaha RD400 (spec infobox and model history)

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Spec	Value	Unit	Source / notes
Oil capacity	1.6	L	Wikipedia, Yamaha RD400 (spec infobox and model history)
Top speed	106.8	mph	Wikipedia, Yamaha RD400 (spec infobox and model history)

Restoration sequence

Same two-stroke discipline as the RD350, with three RD400-specific traps added: the 1976 wheel/rear-brake pairing, E-year carburettor revisions, and ignition type that changes by year and market. Bench order: document, identify by prefix (1A1 vs 2V0), crank-seal leak-down, top end, carbs (year-correct), ignition (year-correct type), Autolube, chassis, brakes.

Step 1 — Document and identify

PREREQUISITE: the factory service manual for your year. System: whole bike. Record the prefix: 1A1 = C/D/E family, 2V0 = US Daytona. Photograph wheels (spoked vs cast) and the rear brake before assuming either — on a 1976 they were an option pair.

Step 2 — Crank seals and leak-down

PREREQUISITE: the factory service manual for your year. System: engine. As the RD350: pressure-test before first start; age-dried seals are the classic stored-RD failure.

Step 3 — Top end

PREREQUISITE: the factory service manual for your year. System: engine. Bore 64 mm, stroke 62 mm — the 400's extra capacity is all stroke, so crank condition matters more here than on a 350. Measure crank runout and big-end play; inspect reed blocks.

Step 4 — Carburettors, year-correct

PREREQUISITE: the factory service manual for your year. System: fuel. 2 x Mikuni 28 mm across the run, but E bikes carry revised carburettor specifications with the porting changes — keep an E's carbs together and do not substitute C/D bodies.

Step 5 — Ignition, year-correct type

PREREQUISITE: the factory service manual for your year. System: electrical. Points on US C/D (and US E per the flagged conflict in the year register); CDI on the US Daytona. Service what is fitted: points get faces/gap/timing per the factory manual; CDI bikes get connector, ground and pulser checks — there are no points to file.

Step 6 — Autolube

PREREQUISITE: the factory service manual for your year. System: oil. Verify pump delivery to both lines and the throttle-linked cable adjustment before loaded running. A starved 400 seizes exactly like a starved 350.

Step 7 — Brakes and wheels

PREREQUISITE: the factory service manual for your year. System: brakes. Front 267 mm disc all years. Rear: drum only on spoked-wheel 1976 C bikes; disc on cast-wheel bikes. Thinner-spoked E/Daytona cast wheels

SAMPLE EXCERPT — full guide available at the link on the cover sheet

crack-check at the spoke roots before refinishing.

Step 8 — Reassembly and break-in

PREREQUISITE: the factory service manual for your year. System: whole bike. Frame-up, fresh fluids, self-cancelling indicator check (the system counts speedo pulses — a dead speedo drive defeats it), gentle heat cycles, varied load.

Finishes, fasteners & markings — the concours details

This is what separates a restoration from a repair. Get these right and judges notice; get them wrong and the bike reads as 'refreshed'.

- Coffin tank shape is RD400-only — an RD350 rounded tank on a 400 is a wrong part, however well painted.
- Documented colours: 1976/77 red sale examples and a blue US 1977; 1979 Daytona white/red is US-1979-only (see Identification). 1978 US colours unverified in cited sources — parts book governs.
- Cast wheels: 1976 option, standard from 1977, thinner-spoked from 1978 — wheel finish work must match the year's wheel.
- Fasteners: metric JIS throughout. Preserve the 1A1-/2V0- stampings; never grind or re-stamp.

Wiring

No generated wiring diagram appears in this guide — a text table is not a wiring diagram, and a wrong diagram is worse than none. Use the **factory service manual's year-correct wiring diagram** as your primary reference.

> *SUPPLEMENT — not a wiring diagram. Trace the factory service manual's year-correct wiring diagram for your bike. The table below maps the major circuits as an inspection aid only; wire colours vary by year and market.*

From	To	Purpose
Battery (+)	Main fuse	Feed
Main fuse	Ignition switch	Switched feed
Ignition switch	Coils / CDI unit (1979 US)	Ignition feed — type is year-specific
Speedometer drive pulses	Flasher cancelling unit	Self-cancelling indicators
Alternator	Regulator / rectifier	Charging
Regulator	Battery (-) / frame	Ground return

Inspection checklist: battery terminals, main fuse holder, ignition switch contacts, coil connections, ground strap to frame/engine, charging connectors. Clean and dielectric-grease every connection you touch.

Tool list

Real tools, honest substitutes. JIS screwdrivers are non-negotiable on a Yamaha of this era.

SAMPLE EXCERPT — full guide available at the link on the cover sheet