

FREE SAMPLE

The opening pages of

1979 Yamaha RD400 Restoration Guide

Read these pages exactly as they appear in the full guide.
Nothing here is rewritten or summarised — it is the product itself,
so you can judge the depth before you spend a dollar.

The full guide: <https://ironheadguides.com/product/IH-YAMAHA-RD400-1979>

IronHead — instant PDF download after checkout.

IRONHEAD

Factory-Correct Restoration Guides

Yamaha RD400

Restoration Guide — Model Year 1979

Engine 399 cc air-cooled two-stroke reed-valve twin	Output 44 bhp @ 7,000 rpm
Brakes Front disc; rear disc or drum by wheel option (1976)	Weight / Tank 165 kg wet / 16.5 L tank (see notes)

Single-year edition — covers the **1979** model year only (RD400F Daytona Special (US designation)). A companion to the Yamaha factory service manual, not a replacement: correct sequence, year-change points, measure-first checkpoints, finishes, fasteners and markings, parts interchange, and honest value guidance.

US \$29.95 • ironhead.polsia.app

About this guide

This is a **restoration companion to the Yamaha factory service manual, not a replacement** for it. You need both: the manual gives the full teardown procedures, torque tables and the wiring diagram; this guide gives you the correct **sequence**, the **model-year change points**, what to **measure before you clean anything**, what **not to do**, the **finishes, fasteners and markings** that make a restoration factory-correct, parts interchange, and honest value guidance.

Every numeric value in this guide is cited to a source in the spec tables. Anything the cited literature does not give a number for is omitted or flagged [**UNVERIFIED — not in factory literature**]. We never invent specifications.

This is a **single-year edition**: it covers the **1979 RD400** only. Do not apply its year-specific details to other years.

Scope: RD400 — model year 1979 (RD400F Daytona Special (US designation))

Yamaha Motor Co. — the context that matters

Yamaha Motor Co. built its reputation on two-strokes: from the 1955 YA-1 the company made light, rev-happy twins its signature, and the RD line carried the TZ racer formula (reed valves, seven ports, Autolube) onto the street (Hagerty Media; Rider Magazine).

For restoration purposes the RD naming matters: the letter after the model (RD350A, RD400C and so on) is the model-year revision, and US designations do not always match rest-of-world ones — the 1979 US Daytona 'F' is the standing warning (Wikipedia, Yamaha RD400).

Yamaha's parts system keys everything to the model-code prefix in the frame number (351-, 1A1-, 2V0- on these bikes). Order by prefix and year, never by model name alone.

Model history — RD400

The RD400 (US model years 1976-1979) grew the RD350 by stroke: a new crankshaft took stroke from 54 mm to 62 mm for 399 cc, with torque the real gain — about 30 lb-ft against the 350's 24 lb-ft (Visordown, Yamaha RD history / RD400 Bike Icon; autoevolution, Yamaha RD model pages).

Styling changed with it: a squared-off 'coffin' tank replaced the RD350's rounded tank (Visordown, Yamaha RD history / RD400 Bike Icon). US models had a smaller, slightly different-shaped tank than other markets (Wikipedia, Yamaha RD400).

The RD400C was the first motorcycle from a major manufacturer offered with cast wheels — as an option in 1976 alongside standard spoked wheels; the choice also decided the rear brake (Wikipedia, Yamaha RD400).

US ignition stayed with points until the Daytona Special; rest-of-world E models are credited with CDI from 1978 — the two statements sit in the same marque record and this guide flags the US position year by year rather than blending them (Wikipedia, Yamaha RD400).

The 1979 Daytona Special closed the US air-cooled RD line; emissions rules ended US sales and the liquid-cooled RD350LC line followed elsewhere (Wikipedia, Yamaha RD400; Mecum Auctions, 1979 RD400 Daytona Special lot record).

Model identification — confirm what you have

Model-code prefixes settle the year: US RD400C/D bikes record 1A1- VINs (Hagerty records: 1976 1A1009049; 1977 1A1314106), and the 1979 US Daytona Special records 2V0- VINs (Hagerty records: 2V0001744 and others; Mecum lot engine no. 2V0001620). The US Daytona is designated 'F' in the USA only — it is not the rest-of-world RD400F (Wikipedia, Yamaha RD400). Read the prefix before anything else: ignition type, wheels and rear brake all follow from it.

This 1979: RD400F Daytona Special (US designation). Frame serial reference: 2V0- prefix (Hagerty records, e.g. VIN 2V0001744; Mecum lot engine no. 2V0001620)

Year-correct equipment: White with red — the Daytona Special scheme: Mecum's lot record lists exterior White/Red; Hagerty records list Silky White / White exteriors across 2V0- sales. This scheme is 1979-US-only.

Confirm the serial block **before ordering parts** — especially brakes, wheels, carburettors and electrics, which are year-specific on this model. A bike titled as one year but carrying another year's major parts is common after 40–60 years; trust the stampings, not the title.

1979 at a glance: Front disc, rear disc

Year-change register — what changed for 1979

Running changes across the model run, with why each matters to a restorer. Rows marked for this year are the ones that affect **your** parts ordering.

- The Daytona Special: the final US RD400 and, per Mecum's lot highlights, the last air-cooled two-stroke sold in the US. White/red paint and Daytona decals are genuine 1979-only identifiers — check the 2V0- prefix, because standard bikes are repainted into this scheme.
- CDI ignition reaches the US line with the Daytona (Wikipedia, Yamaha RD400: US points until the Daytona).
- US 'F' warning: the US Daytona's F designation has no relation to the rest-of-world 1979 RD400F (Wikipedia, Yamaha RD400) — parts ordered as 'RD400F' may be the wrong market's parts.
- Engine carried over at 399 cc / 44 bhp claimed; six-speed, Autolube, disc brakes both ends.

Verified spec tables — 1979 RD400

Every row cites its source. Rows flagged [UNVERIFIED] are printed as found, not as factory-verified. Year band: RD400F Daytona Special (US designation).

ENGINE

Spec	Value	Unit	Source / notes
Engine type	Air-cooled two-stroke parallel twin, reed-valve (Torque Induction)		Wikipedia, Yamaha RD400 (spec infobox and model history)
Displacement	399	cc	Wikipedia, Yamaha RD400 (spec infobox and model history) (autoevolution lists 398 cc — same engine, rounding)

Spec	Value	Unit	Source / notes
Bore x stroke	64 x 62	mm	Wikipedia, Yamaha RD400 (spec infobox and model history)
Compression ratio	6.2:1		Wikipedia, Yamaha RD400 (spec infobox and model history)
Max power (claimed)	44 @ 7,000	bhp @ rpm	Wikipedia, Yamaha RD400 (spec infobox and model history) (Bike magazine, May 1979, as cited; autoevolution quotes 44 @ 7,500 — conflict flagged)
Max torque (claimed)	41.1 (30.3 lb-ft) @ 6,500	N·m @ rpm	Wikipedia, Yamaha RD400 (spec infobox and model history)
Carburettors	2 x Mikuni 28 mm		autoevolution, Yamaha RD model pages (RD400C) / motorbike-search-engine.co.uk, Yamaha RD400 data (1978)
Lubrication	Autolube oil injection, separate tank and pump		Wikipedia, Yamaha RD400 (spec infobox and model history)
Transmission	6-speed, chain drive, kick start		Wikipedia, Yamaha RD400 (spec infobox and model history)

ELECTRICAL

Spec	Value	Unit	Source / notes
Ignition	Points (US, 1976-78); CDI — see year register (1978 E conflict; US Daytona 1979)		Wikipedia, Yamaha RD400 (spec infobox and model history)

CHASSIS

Spec	Value	Unit	Source / notes
Frame	Tubular twin-cradle steel		Wikipedia, Yamaha RD400 (spec infobox and model history)
Front brake	Single disc, 267 mm	mm	autoevolution, Yamaha RD model pages / motorbike-search-engine.co.uk, Yamaha RD400 data
Rear brake	1976: drum with spoked wheels, 267 mm disc with cast-wheel option; disc thereafter — see year register		Wikipedia, Yamaha RD400 (spec infobox and model history) / autoevolution, Yamaha RD model pages
Tyres	3.00 x 18 front / 3.50 x 18 rear (infobox); 1978 listing: 3.60 x 18 / 4.10 x 18 — conflict flagged		Wikipedia, Yamaha RD400 (spec infobox and model history) / motorbike-search-engine.co.uk, Yamaha RD400 data
Wheelbase	1,330	mm	Wikipedia, Yamaha RD400 (spec infobox and model history)
Wet weight	165 (364 lb, part-fuelled figure as cited)	kg	Wikipedia, Yamaha RD400 (spec infobox and model history)
Fuel capacity	16.5 (US tank smaller/different shape — exact US figure [UNVERIFIED])	L	Wikipedia, Yamaha RD400 (spec infobox and model history)
Oil capacity	1.6	L	Wikipedia, Yamaha RD400 (spec infobox and model history)
Top speed	106.8	mph	Wikipedia, Yamaha RD400 (spec infobox and model history)

Restoration sequence

Same two-stroke discipline as the RD350, with three RD400-specific traps added: the 1976 wheel/rear-brake pairing, E-year carburettor revisions, and ignition type that changes by year and market. Bench order: document, identify by prefix (1A1 vs 2V0), crank-seal leak-down, top end, carbs (year-correct), ignition (year-correct type), Autolube, chassis, brakes.

Step 1 — Document and identify

PREREQUISITE: the factory service manual for your year. System: whole bike. Record the prefix: 1A1 = C/D/E family, 2V0 = US Daytona. Photograph wheels (spoked vs cast) and the rear brake before assuming either — on a 1976 they were an option pair.

Step 2 — Crank seals and leak-down

PREREQUISITE: the factory service manual for your year. System: engine. As the RD350: pressure-test before first start; age-dried seals are the classic stored-RD failure.

Step 3 — Top end

PREREQUISITE: the factory service manual for your year. System: engine. Bore 64 mm, stroke 62 mm — the 400's extra capacity is all stroke, so crank condition matters more here than on a 350. Measure crank runout and big-end play; inspect reed blocks.

Step 4 — Carburettors, year-correct

PREREQUISITE: the factory service manual for your year. System: fuel. 2 x Mikuni 28 mm across the run, but E bikes carry revised carburettor specifications with the porting changes — keep an E's carbs together and do not substitute C/D bodies.

Step 5 — Ignition, year-correct type

PREREQUISITE: the factory service manual for your year. System: electrical. Points on US C/D (and US E per the flagged conflict in the year register); CDI on the US Daytona. Service what is fitted: points get faces/gap/timing per the factory manual; CDI bikes get connector, ground and pulser checks — there are no points to file.

Step 6 — Autolube

PREREQUISITE: the factory service manual for your year. System: oil. Verify pump delivery to both lines and the throttle-linked cable adjustment before loaded running. A starved 400 seizes exactly like a starved 350.

Step 7 — Brakes and wheels

PREREQUISITE: the factory service manual for your year. System: brakes. Front 267 mm disc all years. Rear: drum only on spoked-wheel 1976 C bikes; disc on cast-wheel bikes. Thinner-spoked E/Daytona cast wheels crack-check at the spoke roots before refinishing.

Step 8 — Reassembly and break-in

PREREQUISITE: the factory service manual for your year. System: whole bike. Frame-up, fresh fluids, self-cancelling indicator check (the system counts speedo pulses — a dead speedo drive defeats it), gentle heat cycles, varied load.

Finishes, fasteners & markings — the concours details

This is what separates a restoration from a repair. Get these right and judges notice; get them wrong and the bike reads as 'refreshed'.

- Coffin tank shape is RD400-only — an RD350 rounded tank on a 400 is a wrong part, however well painted.
- Documented colours: 1976/77 red sale examples and a blue US 1977; 1979 Daytona white/red is US-1979-only (see Identification). 1978 US colours unverified in cited sources — parts book governs.
- Cast wheels: 1976 option, standard from 1977, thinner-spoked from 1978 — wheel finish work must match the year's wheel.
- Fasteners: metric JIS throughout. Preserve the 1A1-/2V0- stampings; never grind or re-stamp.

Wiring

No generated wiring diagram appears in this guide — a text table is not a wiring diagram, and a wrong diagram is worse than none. Use the **factory service manual's year-correct wiring diagram** as your primary reference.

SUPPLEMENT — not a wiring diagram. Trace the factory service manual's year-correct wiring diagram for your bike. The table below maps the major circuits as an inspection aid only; wire colours vary by year and market.

From	To	Purpose
Battery (+)	Main fuse	Feed
Main fuse	Ignition switch	Switched feed
Ignition switch	Coils / CDI unit (1979 US)	Ignition feed — type is year-specific
Speedometer drive pulses	Flasher cancelling unit	Self-cancelling indicators
Alternator	Regulator / rectifier	Charging
Regulator	Battery (-) / frame	Ground return

Inspection checklist: battery terminals, main fuse holder, ignition switch contacts, coil connections, ground strap to frame/engine, charging connectors. Clean and dielectric-grease every connection you touch.

Tool list

Real tools, honest substitutes. JIS screwdrivers are non-negotiable on a Yamaha of this era.

Tool	Qty	Spec / example	Purpose
JIS screwdriver set	1	Vessel or Hozan JIS	Case and carb screws
Leak-down / crankcase pressure tester	1	Two-stroke type	Crank-seal check
Dial indicator	1	—	Crank runout (62 mm-stroke crank)
Feeler gauges	1	Metric	Points gap (points years) per factory manual
Timing light	1	—	Ignition timing check