FREE SAMPLE

The opening pages of

1977 Yamaha XS650 Buyer's Guide

Read these pages exactly as they appear in the full guide.
Nothing here is rewritten or summarised — it is the product itself,
so you can judge the depth before you spend a dollar.

The full guide: https://ironheadguides.com/product/IH-YAMAHA-XS650-1977

IronHead — instant PDF download after checkout.

IRONHEAD

The 1977 Yamaha XS650D

Factory-Correct Restoration Guide — IronHead

KEY FACTS AT A GLANCE

- **Model year covered:** 1977 only (XS650D, model code 1T3). The factory-service-manual year: Yamaha's supplementary service manual documents the D in full; this guide does not cover the 1976 XS650C or 1978 models except where differences are explicitly noted.
- **Engine:** 654 cc air-cooled SOHC 360° parallel twin; 75.0 mm × 74.0 mm bore × stroke; 8.4:1 compression; 53 bhp @ 7,000 rpm; 39.78 ft-lbs @ 6,000 rpm.
- **Fuel system:** Two Mikuni BS38 constant-velocity carburetors (factory jetting for the D: #122.5 main jet; market variants #117.5/#112.5).
- **Ignition:** Battery-and-coil breaker-point ignition with mechanical advance.
- **Starting:** Electric starter + kick starter.
- **Transmission:** 5-speed constant-mesh manual; primary reduction 72/27 (2.667); ratios 1st 2.462, 2nd 1.588, 3rd 1.300; chain final drive; wet multi-plate clutch.
- **Brakes:** Dual 267 mm front discs, calipers behind fork legs; 180 mm rear drum.
- **Wheels/tires:** Takasago light-alloy rims, wire-spoked; 3.50H-19 front (B.S./Yokohama Y-986), 4.00H-18 rear (Y-987) per the factory manual.
- **Dimensions:** 1,435 mm (56.5 in) wheelbase; 15.0 L (4.0 US gal) fuel capacity; 212 kg (467 lb) weight.
- **1977 colors (US):** Maxi Maroon or Bountiful Blue.
- **Frame/engine serials:** 447- prefix; the 1977 US allocation began at 447-700101.
- **Key 1977-only features:** rectangular brake-fluid reservoir; Maxi Maroon/Bountiful Blue paint; the last year before the 35 mm forks and floating calipers.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

The Yamaha story

Yamaha's history is summarized in full in the IronHead Yamaha manufacturer guide; the key points relevant to this restoration:

- Yamaha Motor Co., Ltd. was founded in 1955, spinning out of Nippon Gakki (the musical-instrument maker) under president Genichi Kawakami.
- Yamaha's first motorcycle was the 1955 YA-1 "Red Dragonfly," a 125 cc two-stroke whose success established the tuning-fork brand in motorcycling.
- Through the 1960s Yamaha built its reputation on two-strokes — the YDS series twins and the TD/TR production racers that dominated small-displacement road racing.
- The XS-1 of 1970 was Yamaha's deliberate four-stroke answer to the Triumph Bonneville and Harley-Davidson Sportster: a 654 cc overhead-cam parallel twin aimed squarely at the American big-bike market.
- By the mid-1970s the XS650 was established as the Japanese alternative to the British twin — and it outlasted them all, running in production from 1970 through 1983.

The XS650 story

The model-line history is summarized here; the sections below cover what makes the 1977 XS650D specifically correct.

- The XS-1 (1970) launched the line: 654 cc SOHC twin, kick-start only, drum brakes front and rear, built to take on Triumph and Harley-Davidson on their home ground.
- The XS-1B (1971) refined the formula in Candy Orange, retaining the front drum brake.
- The XS-2 (1972) added the electric starter and a 298 mm front disc — the first major mechanical revision.
- The TX650 (1973) brought the larger 14 L tank and a front end provisioned for a second disc.
- The TX650A (1974) was the Percy Tait chassis revolution: longer swingarm, repositioned engine, dual 267 mm front discs, and a stronger starter with the compression release deleted.
- The XS650B (1975) restored the XS name; the XS650C (1976) moved the front calipers behind the fork legs.
- The XS650D (1977) is the best-documented Standard — Yamaha's supplementary service manual was written for it.
- 1978 split the line: the XS650E Standard (the last roadster) and the XS650SE Special (the first factory custom), both on 35 mm forks with floating calipers.
- 1979 ran three variants — F Standard, SF Special (with rear disc), and the 2F Special II — the last year of points ignition and BS38 carburetors.
- 1980 brought transistorized TCI electronic ignition and Mikuni BS34 carburetors; the lineup became Specials only.
- 1981 (H/SH) carried the formula with new colors; 1982–83 closed the line as the Heritage Special (SJ/SK).
- Total XS650 production exceeded 500,000 units across the fourteen model years.

What makes the 1977 unique

The XS650D is the best-documented Standard of the line — Yamaha's factory supplementary service manual was written for the D, which means the restorer has genuine factory torque figures, jetting, gear ratios, and service intervals to work from rather than enthusiast transcriptions. Mechanically it is the refined end of the B–C–D evolution: the Tait chassis, dual 267 mm discs with behind-the-fork calipers, BS38 carburetors, and points ignition.

1977-only details:

SAMPLE EXCERPT — full guide available at the link on the cover sheet

- **Rectangular brake-fluid reservoir.** The US-market D carries the

rectangular master-cylinder reservoir — the visual tell that separates a 1977 from the 1976 at the handlebar.

- **Maxi Maroon or Bountiful Blue.** The two US colorways.
- **Model code 1T3**, US serials from 447-700101.
- **Last of the 34 mm forks and opposed-piston calipers.** For 1978 Yamaha

moved to 35 mm stanchions and floating single-piston calipers — so the D is the final year of the original second-generation front end.

What carried over: everything else from the C — engine, BS38s, points, gearbox, Takasago rims, 15.0 L tank, Tait frame.

1977 buyer cautions:

- **Use the factory manual.** The D's supplementary service manual is the

genuine article — torque figures, jetting, and intervals in Section 4 below come straight from it. Beware generic "XS650 manual" PDFs that mix years; the D supplement is the one written for this bike.

- **Maroon vs. blue trim.** Both 1977 colors used the same black trim scheme;

verify side-cover and tank badges against the fiche — the two colors' badges are year-specific.

- **Opposed-piston caliper seals.** The twin-opposed-piston calipers are

superb stoppers but their seals harden with age. A full caliper rebuild (seals, pistons inspected for pitting) is mandatory on any unknown-history D, not optional.

Serial numbers and model codes

Model year: 1977 · Designation: XS650D · Model code: 1T3. Frame and engine serials: 447-700101 onward (1977 US allocation). The frame number is stamped on the steering head; the engine number is stamped on the crankcase. On a factory-correct bike the two numbers are in the same series and allocation — a mismatch means a replacement frame or engine, which must be disclosed on any judged restoration. Decode carefully: the serial prefix (e.g. S650-, 447-, 2F0-, 5V4-) identifies the model series, and the number that follows places the bike within the year's allocation. The XS650D's prefix is 1T3-series as listed above; any other prefix on the frame or engine means the component is not original to this model year.

Engine and internals

654 cc (1982–83 Specials: 653 cc) air-cooled SOHC 360° parallel twin. Bore × stroke 75.0 mm × 74.0 mm; compression ratio 8.4:1 (per the factory figures for this year); output ~53 bhp. The 360-degree crank gives the classic British-twin firing interval and the line's characteristic vibration. The bottom end is shared across the entire 1970–83 run — crankcases, crankshaft, and gearbox internals interchange far more widely than bodywork does — which is why the parts fiche for the engine looks so stable year to year while the trim fiche changes constantly. Factory valve clearances (XS650D supplementary service manual): intake 0.10 mm (0.004 in), exhaust 0.15 mm (0.006 in), checked cold. Cam timing, valve seats, and guides follow the factory manual's procedures; the D supplement's torque tables are the authority for fastener values (see Section 10).

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Fuel system

Carburetors: 2 × Mikuni BS38 constant-velocity (factory D jetting: #122.5 main; market variants #117.5/#112.5). Points-era bikes (1970–79) run Mikuni BS38s; TCI-era bikes (1980–83) run BS34s. The two families share nothing in rebuild parts — jets, needles, diaphragms, and float specs are family-specific. Identify the carbs by the body stamping before ordering anything. Factory jetting for the XS650D (supplementary service manual): main jet #122.5, with market variants #117.5 and #112.5 — the manual explicitly documents all three. Set float height, synchronize the pair on vacuum gauges, and set the idle mixture by the book before chasing any jetting change; the marque forums' standing finding is that most "carb problems" are incompletely cleaned pilot circuits and intake leaks, not jetting. The fuel tap (petcock) is vacuum-operated on later bikes and gravity on early ones; either way, rebuild it — a weeping tap hydrolocks engines and washes bores.

Electrical system

Ignition: Breaker points with mechanical (centrifugal) advance. Starting: Electric starter + kick starter. Breaker-point maintenance is the standing task: set the points gap, verify the mechanical advance moves freely and springs back (weak springs retard the curve and flatten the midrange), replace condensers on any unknown-history bike, and static-time then strobe-time the ignition. The charging system is the known weak point of the early bikes — the marque community's standing advice is to load-test the rotor and stator, replace the rectifier/regulator with a modern combined unit, and clean every bullet connector. Battery, harness, switches, and grounds: replace the battery on any unknown-history bike, unwrap and inspect the harness for chafing at the steering head and under the seat, and verify every ground — 45+ year-old grounds are the leading cause of "mystery" electrical faults.

Transmission and driveline

5-speed constant-mesh manual gearbox. Primary reduction 72/27 (2.667). Factory gear ratios (D supplement): 1st 2.462, 2nd 1.588, 3rd 1.300, 4th and 5th per the manual's table; final drive by roller chain. Clutch: wet multi-plate. Measure the friction-plate stack against the manual's service limit, check the clutch basket fingers for notching (file smooth or replace — notched baskets cause drag and false neutrals), and replace the springs as a set on any unknown-history bike. Chain and sprockets: replace as a set. Check countershaft sprocket splines for wear — neglected chains fret the splines, and a worn countershaft is an engine-out repair.

Brakes

Dual 267 mm front discs (twin-opposed-piston calipers, behind fork legs); 180 mm rear drum. Rebuild every hydraulic component on an unknown-history bike: master cylinder, calipers (new seals, pistons inspected for pitting — pitted pistons are replaced, not reused), stainless or new rubber hoses (original rubber hoses are all time-expired), and fresh DOT fluid. 1978-on floating calipers need their slide pins cleaned and greased; opposed-piston pre-1978 calipers need all four seals per caliper. Discs: measure thickness and runout against the manual's limits. Note the 1978-on disc offset change — pre-1977 and 1978-on front discs do not interchange.

Wheels, forks, and suspension

Wheels: Takasago light-alloy rims, wire-spoked; 3.50H-19 front, 4.00H-18 rear (factory spec). Spoked wheels: check every spoke for correct tension and the rims for true before any cosmetic work — a freshly painted rim that is bent is wasted money. Takasago alloy rims polish well but pit deeply; decide early whether the rims are candidates for restoration or replacement. Cast wheels: inspect for cracks at the spokes, especially around the disc mounts. Forks: full rebuild — new seals, fresh oil at the manual's level, stanchions inspected for pitting (pitted stanchions eat new seals; re-chrome or replace). Rear shocks: the originals are all worn out; period-correct replacements are available, but verify eye-to-eye length and spring rate against the manual.

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Paint, trim, and finishes

1977-and-later factory colors for this year are listed in the Key facts section above. Paint codes and stripe layouts are year-specific — verify against the parts fiche for the XS650D, not against a generic XS650 reference. Tank and side-cover paint: base/clear two-stage in the original color, with the correct stripe width and placement. Badges are year-specific — the 1977 badges differ from neighboring years in script, color, or mounting. Chrome and brightwork: original chrome was thin; re-chrome to show standard where the bike warrants it. Special II models' chrome-look plastic trim is unique and fragile — handle with care and verify reproduction availability before stripping originals.

Torque specifications

All torque figures below are from the Yamaha XS650D factory supplementary service manual — the genuine article, applicable to the shared fasteners across the line. Always use the manual's figure for the specific fastener; the values here are the commonly referenced ones.

Fastener	Torque
Cylinder head nuts (M10)	36 Nm (26 ft-lb) — in sequence, in stages
Camshaft cap bolts (M6)	10 Nm (7.2 ft-lb)
Cam sprocket bolt	40 Nm (29 ft-lb)
Crankcase bolts (M6)	10 Nm (7.2 ft-lb)
Crankcase bolts (M8)	20 Nm (14.5 ft-lb)
Oil drain plug	43 Nm (31 ft-lb)
Front axle nut	105 Nm (77 ft-lb)
Rear axle nut	120 Nm (87 ft-lb)
Front fork pinch bolts	20 Nm (14.5 ft-lb)
Handlebar clamp bolts	23 Nm (17 ft-lb)
Brake caliper mounting bolts	40 Nm (29 ft-lb)
Rear brake torque arm nut	25 Nm (18 ft-lb)
Sprocket nuts	60 Nm (43 ft-lb)
Spark plugs	20 Nm (14.5 ft-lb)

Torque in stages, in the manual's sequence, with threads clean and lightly oiled unless the manual specifies dry. Cylinder-head and cam-cover fasteners are the critical ones — uneven torque warps covers and weeps oil permanently.

Service schedule and wear items

Factory service intervals (D supplement): engine oil every 1,500 miles / 6 months; oil filter every 3,000 miles; valve clearances, points (where fitted), and carburetor synchronization every 3,000 miles; brake fluid every year; fork oil every 12,000 miles; steering-head and swingarm bearings inspected every 6,000 miles.

Item	Spec / interval
Engine oil (with filter change)	2.5 L — SAE 20W-40/20W-50, every 1,500 miles
Final drive chain	Clean, lube, and adjust every 300 miles

SAMPLE EXCERPT — full guide available at the link on the cover sheet

Item	Spec / interval
Valve clearances	IN 0.10 mm / EX 0.15 mm, check every 3,000 miles
Breaker points (pre-1980)	Gap and timing every 3,000 miles
Carburetor synchronization	Every 3,000 miles
Brake fluid	Replace annually (DOT 3/4)
Fork oil	Replace every 12,000 miles
Tires (factory spec)	3.50H-19 front, 4.00H-18 rear (D supplement)

Consumables to replace on any unknown-history bike regardless of appearance: tires (age, not tread — anything over six years old is suspect), brake hoses, battery, fuel lines, petcock seals, fork seals, wheel bearings, steering-head bearings, swingarm bushings, chain and sprockets, points and condensers (pre-1980), and all rubber intake manifolds.

Rust-prone areas and inspection points

Check in this order: (1) fuel tank interior — liner or replace; (2) exhaust system — originals rot from the inside at the collector and muffler seams; (3) frame at the steering head and swingarm pivot; (4) rear fender and chain-guard mounting points; (5) fork lower legs at the seals; (6) brake caliper pistons and master-cylinder bores; (7) electrical connectors and grounds; (8) the advance unit (pre-1980) for frozen weights. Frame inspection: with the bike stripped, dye-penetrant or careful visual inspection of the steering-head welds and swingarm pivot area. Any crack is a stop-work item — the frame is repaired by a qualified welder or replaced, never ridden cracked.

Restoration sequence

Step 1: Document and photograph everything before disassembly — cable routing, fastener positions, wiring runs. Bag and tag every fastener by assembly. **Step 2:** Assess the frame and running gear first: check the frame for cracks and straightness, then rebuild the rolling chassis (bearings, brakes, forks, wheels) before the cosmetics. **Step 3:** Engine: full strip, measure everything against the factory manual's service limits. The bottom end is robust; budget for valve seats, guides, and a rebore only if measurements demand it. **Step 4:** Carburetors: ultrasonic clean, all new soft parts, set to factory jetting and float height before any tuning. Do not re-jet to fix what is actually an intake leak or weak spark. **Step 5:** Electrical: rebuild the harness or replace it — 45+ year-old wiring is not trustworthy. Points-era bikes get new points, condensers, and advance-unit service; TCI-era bikes get connector hygiene and igniter/pickup testing. **Step 6:** Paint and plating: bodywork painted in the correct year color with correct stripes and badges; chrome re-plated to show standard; fasteners correctly finished (zinc, black, or plain as original). **Step 7:** Reassembly in the factory sequence, torqued to the manual's figures, with all fluids fresh and every adjustment set to spec. **Step 8:** Shakedown: 500 careful miles with frequent checks, then re-torque the head, re-check valve clearances, re-synchronize the carbs, and change the oil. The bike is finished when it starts, idles, and stops like Yamaha intended.

Sources and further reading

- Yamaha XS650D supplementary service manual (factory) — torque tables, BS38 jetting, gear ratios, valve clearances, tires, service chart, brake data.
- Yamaha XS650 shop manual (factory mirror) — general service procedures and specifications.
- Yamaha XS650 owner's manuals (factory) — operation, maintenance schedule, capacities.
- Yamaha parts fiches/catalogs by model code (S650-, 447-, 2F0-, 2M0-, 3N0-, 3G0-, 4N9-, 4M4-, 5V4-) — serial allocations, paint/trim, part interchange.
- XS650 model-ID table (xs650chopper.com) — US model codes, serial starts, colorways.

SAMPLE EXCERPT — full guide available at the link on the cover sheet